



Engine Armour Tech™ is an environmentally safe, non-flammable, inert formulation does not contain any V.O.C.'s, no solvents, silicone, graphite, molybdenum or PTFE's. Will not effect or change the viscosity of any OEM recommended fluids and **will not allow** the formulation of sludge and abrasive carbon

Engine Armour Tech™ reduces toxic emissions by as much as 92% from Hydrocarbon, NOx, PM, & Carbon Monoxide.

Gasoline and Diesel Engine

1. Warm Engine to it's operating temperature.
2. Add the required dosage to the engine oil.
3. Start engine and drive a minimum of 30 km. 40km for Diesels, preferably highway driven.

NOTICE:

if applied to used Oil, allow Engine Armour Tech™ to flow in the oil for minimum 2000 km.

Gearbox and Diferentials

1. Add the required dosage before operating.

Automatic Transmissions

1. Warm Engine to it's operating temperature.
2. Add the required dosage to transmission oil.
3. Start engine and drive a minimum of 30 km.

NOTICE: Always have an automatic transmission profesional check and remove fluid if necessary before application to prevent overfill.



Diesel Engines

+300 HP + 16 oz

-300 HP - 8 oz

18L & up add 2 oz to every 5 Litres

3 oz for Automatic Transmission
8 oz for Manual Transmissions

